



US005635235A

**United States Patent** [19]

Sanchez et al.

[11] Patent Number: 5,635,235

[45] Date of Patent: Jun. 3, 1997

## [54] METHODS FOR HANDLING MASA

[75] Inventors: Victor R. Sanchez, Fontana; Alberto Ceja, Pico Rivera; Rigoberto Anguiano, Baldwin Park, all of Calif.

[73] Assignee: Machine Masters, Inc., Pomona, Calif.

[21] Appl. No.: 476,198

[22] Filed: Jun. 7, 1995

## Related U.S. Application Data

[62] Division of Ser. No. 192,458, Feb. 7, 1994.

[51] Int. Cl.<sup>6</sup> A21C 9/00

[52] U.S. Cl. 426/496; 426/502; 426/503; 426/512; 426/518; 99/443 C; 99/353; 198/604; 198/607; 198/626.1; 221/84

[58] Field of Search 426/391, 496, 426/502, 503, 516-518, 512, 549; 99/443 C, 352, 353; 198/604, 607, 626.1; 221/71, 74, 84

## [56] References Cited

## U.S. PATENT DOCUMENTS

3,693,533	9/1972	Liepa	99/234
3,853,016	12/1974	Lane, III et al.	74/231
3,869,971	3/1975	Driscoll	99/353
4,304,326	12/1981	Fowler	198/623
4,334,845	6/1982	Tamminen	99/353 X
4,640,843	2/1987	Matuszak et al.	426/560
4,661,364	4/1987	Campbell	426/496
4,778,690	10/1988	Sadel, Jr. et al.	426/560
4,978,548	12/1990	Cope et al.	426/439
4,985,269	1/1991	Irvin et al.	426/560

5,050,727	9/1991	Akesaka	198/626.1
5,158,792	10/1992	Monikawa et al.	426/503 X
5,200,203	4/1993	Hayashi	198/604 X
5,272,962	12/1993	Kageyama et al.	99/353

Primary Examiner—Milton Cano

Attorney, Agent, or Firm—Keith A. Newbury, Esq.; Pretty, Schroeder, Brueggemann & Clark

## [57] ABSTRACT

Masa handling methods for the continuous processing of masa type dough in conjunction with commonly available feed processing equipment, such as a masa extruder, an oven, or cooling apparatus. One masa handling method includes a masa separator having a pair of opposed, endless belt conveyors having facing surfaces spaced apart to receive a generally continuous masa stream output from a nozzle on the masa extruder. When the masa stream moves between the conveyors, it is gripped by their facing surfaces and moved away from the nozzle, causing the masa to be separated into individual pieces, or logs. The masa handling method can also include feeding the masa to masa hoppers fed by at least two endless belt conveyors arranged in upstream and downstream positions relative to each other. The masa is transported along the conveyors and is automatically diverted into one masa hopper by a diverter gate operated by a controller that receives a signal from a sensor sensing a masa level within an associated one of the hoppers. The hopper has one or more rotating shafts having projections to remove gas bubbles from the masa and force it toward the sheeter rollers. A pair of primary rollers with scrapers can be provided within the hopper to roll the masa to an intermediate thickness before it passes between the sheeter rollers.

20 Claims, 4 Drawing Sheets

